



MIDWAY SANDBLAST HOSE

MIDWAY HOSE ASSEMBLY CENTER

4040 New Court Ave
Syracuse, NY 13206

Phone
315.272.2300 hose
315-272-2302 ind'l

MIDWAYCORP.COM



Application	Sandblast hose with abrasion resistant tube quality for conveying abrasive media such as quartz sand, steel shot, corundum, glass, etc.
Feature	Long service life due to abrasion resistant tube. Average wear of the tube 70mm (according to DIN ISO 4649:2021). Antistatic construction prevents the build-up of static electricity.
Temperature Range	-31°F / +176°F (-35°C / +80°C).
Safety Factor	3 : 1
Tube	NR/BR/SBR, black, abrasion resistant, antistatic, smooth.
Reinforcement	Textile wrapped.
Cover	SBR, black, resistant to ozone and weather, antistatic, cloth impression.
Marking	Continuous mylartape, black background / white letters "MIDWAY SANDBLAST - 1-1/4" 2-PLY 175psi MAX W.P."
Notice	200ft length available upon request.

PART NUMBER	DESCRIPTION	INTERNAL-O (ID)	WALL WIDTH	EXTERNAL-O (OD)	WORK PRESSURE (MAX)	NUMBER OF INSERTS	BENDING RADIUS (MIN)	WEIGHT APPROX.	COIL LENGTH
50SBH2PX100	1/2" 2PLY	1/2"	.28"	1-1/16"	175 PSI	2	5"	0.35 LB/FT	100 FT
50SBH4PX100	1/2" 4PLY	1/2"	.28"	1-3/16"	175 PSI	4	5"	0.35 LB/FT	100 FT
SPECIAL *	3/4" 2PLY	3/4"	.37"	1-1/2"	175 PSI	2	7.5"	0.67 LB/FT	100 FT
75SBH4PX100	3/4" 4PLY	3/4"	.37"	1-1/2"	175 PSI	4	7.5"	0.67 LB/FT	100 FT
100SBH2PX100	1" 2PLY	1"	.25"	1-1/2"	175 PSI	2	10"	0.78 LB/FT	100 FT
100SBH4PX100	1" 4PLY	1"	.44"	1-7/8"	175 PSI	4	10"	0.99 LB/FT	100 FT
125SBH2PX100	1-1/4" 2PLY	1-1/4"	.31"	1-7/8"	175 PSI	2	12.5"	0.79 LB/FT	100 FT
125SBH4PX100	1-1/4" 4PLY	1-1/4"	.45"	2-5/32"	175 PSI	4	12.5"	1.20 LB/FT	100 FT
150SBH4PX100	1-1/2" 4PLY	1-1/2"	.44"	2-3/8"	175 PSI	4	15"	1.37 LB/FT	100 FT
200SBH4PX100	2" 4PLY	2"	.44"	2-7/8"	175 PSI	4	20"	1.73 LB/FT	100 FT

* AVAILABLE BY SPECIAL ORDER ONLY

